# **BluePad-55**

Mobile Pinpad and Barcode Reader Attachment







#### BluePad-55

BluePad-55 is a new entry in the pinpad series, which introduces a bigger, colorful touch screen display and a higher capacity battery. It offers Bluetooth for all types of card payment magnetic stripe, EMV Chip&PIN and contactless.

The contact pads provide easy installation of accessories such as a barcode scanner, a mobile printer and a charging dock.

#### **BlueScan-55**

An accessory that connects via the contact pins on the back of the device to allow for fast and reliable scanning.





#### **BluePrint-55**

A stand-alone mobile printed which cradles a BluePad-55 or connects via Bluetooth to provide printed clie receipts.

**BlueCharge-55** 

A charging station compatible with both BluePrint-55 and BluePad-55.





## BluePad-55

### **BlueScan-55**

Operator Display	2.4 inch Touch Caroon 220 v 240 pv	0D Davida Davidar	
	2.4-inch Touch Screen 320 x 240 px	2D Barcode Reader	Opticon MDI-4000 - 640 x 480 CMOS
Magnetic Card Reader	Triple track bi-directional	Device Compatibility	BluePad-55
Smart Card Reader	Landing type	Power Supply	DC 5 V through contact pins
Contactless Reader (optional)	ISO/IEC 14443 Type A MIFARE Mini MIFARE Classic 1K MIFARE Classic 4K MIFARE Ultralight MIFARE Ultralight C MIFARE Plus 2K MIFARE Plus 4K MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC	Dimension W x D x H	81 x 52 x 26 mm
		Weight	30 g
		Blue	ePrint-55
		Printing Mechanism	Seiko Instruments LTP01-245-05
Contactless Payments (optional)	VISA payWave MasterCard Contactless American Express ExpressPay Discover D-Pas UnionPay QuickPass JCB J/Speedy	Printing Speed	12 lines per second
		Paper Width	58 mm
		Paper Thickness	60 to 72 µm
		Max Roll Diameter	50 mm
Connectors	RS-232 contact pins USB Type-C port SAM card slot (optional) SIM card slot (optional)	Connectors	USB Type-C port Contact pins (cradle)
		Wired Communication	USB (device)
Wired Communication	USB (device)	Device Compatibility	BluePad-55
Bluetooth (optional)	BT version 4.2 Low Energy	Power Supply	DC 5 V through contact pins
Wireless (optional)*	Wi-Fi IEEE 802.11 b/g/n	Detterr	DC 5 V through USB
Modem (optional)*	3G communication	Battery	Rechargeable Li-Ion Battery 3.6 V, 2160 mAh
OS Compatibility	iOS Android Windows	Dimension W x D x H	80 x 191 x 55 mm
		Weight	245 g
Power Supply	DC 5 V through USB DC 5 V through contact pins	_	_
Battery	Rechargeable Li-Ion Battery 3.7 V, 1180 mAh Fuel Gauge	Blue	Charge-55
Certificates	CE	0	
Centilicates	FCC PCI PTS 4.x EMV Level 1, EMV Level 2 EMV Level 1 Contactless	Connectors	Contact pins (cradle)
		Device Compatibility	BluePad-55 BluePrint-55
Dimension W x D x H	71 x 133 x 19 mm	Power Supply	AC 100 to 240 V, 50 to 60 Hz, DC 5 V, 3 A
Weight		Dimension W x D x H	90 x 198 x 28 mm
* DueDed 55 effere e obside both	100 g	Weight	130 g

\* BluePad-55 offers a choice between the Wi-Fi and Modem options.