

# LineaPro 15 Industrial

<b>CPU</b>	ARM Cortex M4
<b>Buttons</b>	2 Scan buttons 2 Push to talk buttons
<b>Contactless Reader</b>	NFC-A, ISO 14443 Type A NFC-B, ISO 14443 Type B ISO/IEC 14443 Type-B ISO/IEC 15693 JIS X 6319-4 ISO/IEC 18000-3 mode 3
<b>Barcode Reader</b>	2D Opticon MDI-4000 640 x 480 (optional) 2D Zebra SE4750 SR/MR 1280 x 960 (optional) 2D Zebra SE4770 1280 x 960 CMOS (optional) 2D Zebra SE5500 CMOS 2688 x 1520 (optional) 2D Megahunt M101H CMOS 640 x 480 (optional)
<b>Symbologies</b>	JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/ Plessey Chinese Post, Intelligent Mail Barcode, Korean Postal Authority code, POSTNET Aztec Code, Aztec Runes, Chinese Sensible code, Codablock F, Composite codes, Data Matrix (ECC200), Passport MRZ (OCR-B), Maxi Code
<b>Connectors</b>	USB Type-C port USB Type -C connector (cradle) SAM holder Docking connector
<b>Wired Communication</b>	Serial communication (USB Type-C port) Serial communication (Docking connector)
<b>Device Compatibility</b>	iPhone 15
<b>Audio Features</b>	Electromagnetic buzzer
<b>Power Supply</b>	DC 5 V through USB type C DC 5 V through docking connector
<b>Battery</b>	Rechargeable Li-Ion Battery 3.6 V, 2330 mAh Fuel Gauge
<b>Dimension W x D x H</b>	83 x 171 x 25 mm
<b>Weight</b>	180 g
<b>Operational Temperature</b>	-10 °C to 40 °C / 5 to 90% RH
<b>Storage Temperature</b>	-20 °C to 50 °C / 5 to 90% RH
<b>Drop Tested</b>	1.2 m faces and edges
<b>Other Box Contents</b>	LineaPro 15 Industrial device USB Type-C cable

